



Technical specifications

Tiller®-liftmobile LM120G



Max. liftcapacity: 120 kg
Liftingspeed: 60 mm/s
Max. liftingheight: 0.80 m

Noseplate depth: 0.23 m
Noseplate width: 0.40 m

Weight: 50 kg
Height: 1.55 m
Width: 0.52 m
Material: coated steel
Tyre size: 4.10/3.50 - 4

Battery type: NiMH
Voltage: 24 V
Charger voltage: 110V - 220V
Recharging time: 8 hours at full discharge, automatically switch to trickle charge

This accessory gives the liftmobile a specific application for handling glass, windows, doors and walls.

Certification

The liftmobile is CE certified. This means that the product complies with the relevant regulations within the European Economic Area (EEA: the European Union plus Liechtenstein, Norway and Iceland).

Machinery Directive (2006/42/EG)
EMC Directive (2004/108/EG)
Low Voltage Directive (2006/95/EG)

For the design and manufacture:
NEN-EN-ISO 12100-1; NEN-EN-ISO 12100-2;
NEN-EN-IEC 60204-1; NEN-EN 574;
NEN-EN 349; NEN-EN-IEC 61000-6-2; NEN-EN-IEC 61000-6-4

For the risk assessment:
NEN-EN-ISO 14121-1; NPR/ISO-TR 14121-2

Tiller BV
Den Haag, Netherlands
+31 (0) 15 - 310 6 999
www.tiller.eu