



## Technical specifications

### Tiller®-liftmobile LM120HA



Max. liftcapacity: 120 kg  
Liftingspeed: 60 mm/s  
Max. liftingheight: 0.80 m (option up to 1.10 m)

Noseplate depth: 0.20 m  
Noseplate width: 0.60 m

Weight: 54 kg  
Height: 1.55 m  
Width: 0.52 m  
Material: coated steel  
Tyre size: 4.10/3.50 - 4

Battery type: NiMH  
Voltage: 24 V  
Charger voltage: 110V - 220V  
Recharging time: 8 hours at full discharge, automatically switch to trickle charge

This accessory gives the liftmobile a specific application for transporting and lifting washing machines (including the Miele washing machines).

#### Certification

The liftmobile is CE certified. This means that the product complies with the relevant regulations within the European Economic Area (EEA: the European Union plus Liechtenstein, Norway and Iceland).

Machinery Directive (2006/42/EG)  
EMC Directive (2004/108/EG)  
Low Voltage Directive (2006/95/EG)

For the design and manufacture:  
NEN-EN-ISO 12100-1; NEN-EN-ISO 12100-2;  
NEN-EN-IEC 60204-1; NEN-EN 574;  
NEN-EN 349; NEN-EN-IEC 61000-6-2; NEN-EN-IEC 61000-6-4

For the risk assessment:  
NEN-EN-ISO 14121-1; NPR/ISO-TR 14121-2

**Tiller BV**  
Den Haag, Netherlands  
+31 (0) 15 - 310 6 999  
[www.tiller.eu](http://www.tiller.eu)