



## Technical specifications

### Tiller®-liftmobile LM75PFS



Max. liftcapacity:	75 kg
Liftingspeed:	100 mm/s
Max. liftingheight:	1.10 m
Noseplate depth:	0.30 m
Noseplate width:	0.46 m
Weight:	48 kg
Height:	1.55 m
Width:	0.52 m
Material:	coated steel
Tyre size:	4.10/3.50 - 4
Battery type:	NiMH
Voltage:	24 V
Charger voltage:	110V - 220V
Recharging time:	8 hours at full discharge, automatically switch to trickle charge

This accessory gives the liftmobile a specific application for transporting and lifting all kinds of plastic and wooden (display) pallets and materials on plastic and wooden (display) pallets.

#### Certification

The liftmobile is CE certified. This means that the product complies with the relevant regulations within the European Economic Area (EEA: the European Union plus Liechtenstein, Norway and Iceland).

Machinery Directive (2006/42/EG)  
EMC Directive (2004/108/EG)  
Low Voltage Directive (2006/95/EG)

For the design and manufacture:  
NEN-EN-ISO 12100-1; NEN-EN-ISO 12100-2;  
NEN-EN-IEC 60204-1; NEN-EN 574;  
NEN-EN 349; NEN-EN-IEC 61000-6-2; NEN-EN-IEC 61000-6-4

For the risk assessment:  
NEN-EN-ISO 14121-1; NPR/ISO-TR 14121-2

**Tiller BV**  
Den Haag, Netherlands  
+31 (0) 15 - 310 6 999  
[www.tiller.eu](http://www.tiller.eu)