



Technical specifications

Tiller®-liftmobile LM75WA



Max. liftcapacity: 75 kg
Liftingspeed: 100 mm/s
Max. liftingheight: 1.10 m

Noseplate depth: 0.50 m
Noseplate width: 0.42 m

Weight: 51 kg
Height: 1.55 m
Width: 0.52 m
Material: coated steel
Tyre size: 4.10/3.50 - 4

Battery type: NiMH
Voltage: 24 V
Charger voltage: 110V - 220V
Recharging time: 8 hours at full discharge, automatically switch to trickle charge

This accessory gives the liftmobile a specific application for transporting, assembling and lifting (car) tires/wheels. The difference with the LM75W is that this type is not equipped with rollers, but with a pin to fix the tire.

Certification

The liftmobile is CE certified. This means that the product complies with the relevant regulations within the European Economic Area (EEA: the European Union plus Liechtenstein, Norway and Iceland).

Machinery Directive (2006/42/EG)
EMC Directive (2004/108/EG)
Low Voltage Directive (2006/95/EG)

For the design and manufacture:
NEN-EN-ISO 12100-1; NEN-EN-ISO 12100-2;
NEN-EN-IEC 60204-1; NEN-EN 574;
NEN-EN 349; NEN-EN-IEC 61000-6-2; NEN-EN-IEC 61000-6-4

For the risk assessment:
NEN-EN-ISO 14121-1; NPR/ISO-TR 14121-2

Tiller BV
Den Haag, Netherlands
+31 (0) 15 - 310 6 999
www.tiller.eu